

## COMPLIANCE

- ANSI/TIA 568-C.2 Category 6A
- ISO/IEC 11801 Class E

## FEATURES & BENEFITS

- Loaded with 24 jacks.
- With rear cable manager for cable management.
- Plenty of tag space, management of port information is clearer and more convenient
- Standard 19", widely used as industry standard



## PHYSICAL CHARACTERISTICS

IDC	Phosphor bronze
RJ45 Pin	Phosphor bronze with 50microinch gold plating
Plug Insertion	≥1000 times
IDC Insertion Life Span	≥250 times
AWG	22~26AWG
Wiring	T568A/T568B

## ELECTRICAL CHARACTERISTICS

Dielectric Strength	DC 1000V(AC750V) 1min,no breakdown and arcing phenomena
DC Resistance (Ω)	≤300mΩ
Connecting Resistance (Ω)	≤20mΩ
Insulation Resistance (Ω)	Under normal atmospheric pressure ≥500mΩ

## NAME CODING



## ORDERING INFORMATION

Part NO.	Description
VPCPSFA241	VIVANCO CAT 6A 24 Port Patch Panel(Shielded, Loaded)
VPCPSFA241A	VIVANCO CAT 6A 24 Port Patch Panel(Shielded, Loaded, Easy Installation)